

#### AZLED/1

Z LED High Bay UFO - 98W - Cool White



### Features

Robust LED low/high bay for industrial, commercial and retail applications Pre-wired with 3m of H07RN-F cable for ease and speed of installation Alternative installation options by means of drop rods, jack chain / catenary wire 98W comparable to 150W HQI Die-cast powder coated construction and heatsink for optimum thermals and performance IP65 as standard IK08 Rating TP(a) as standard LED lifespan L70 50,000 hours



## **General Information**

Lamp Type	LED
Colour / Finish	Black
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Suspended
LED Life	L70 50,000hrs
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	320
Depth (mm)	30

# **Technical Information**

Lumens Delivered     11858lm       Lm/W     121lm       CRI     Ra 80       CCT     4000K       Input     200-240V       Hertz     50/60Hz		
Lm/W   121lm     CRI   Ra 80     CCT   4000K     Input   200-240V     Hertz   50/60Hz	Wattage	98W
CRI   Ra 80     CCT   4000K     Input   200-240V     Hertz   50/60Hz	Lumens Delivered	11858lm
CCT 4000K   Input 200-240∨   Hertz 50/60Hz	Lm/W	121lm
Input     200-240V       Hertz     50/60Hz	CRI	Ra 80
Hertz 50/60Hz	ССТ	4000K
	Input	200-240V
Operating Temp -40°C to 50°C	Hertz	50/60Hz
	Operating Temp	-40°C to 50°C



### Technical Data - ETIM 6 - High bay luminaire (EC001716)

With light source	Yes
Suitable for number of lamps	1
Lamp power	98 W
Lamp power at multiwatt	Not applicable
Control gear included	Yes
Suitable for emergency lighting	Νο
Nominal voltage	200-240 V
Material housing	Aluminium
Mounting method	Pendant
Type of grid	None
Height/depth	178 mm
Diameter	320 mm
Protection class	1
Degree of protection (IP)	IP65
Impact strength	IK08
Rated luminous flux acc. IEC 62722-2-1	11858 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89

Datasheet generated from https://www.electrika.com last updated Friday, June 7, 2019 12:33:53 PM





