Ei146e

Optical Smoke Alarm



- Optical sensor quick response to slow smouldering fires
- Automatic dust compensation
- Mains powered with 9V Alkaline battery back-up
- Easi-fit base for quick and simple installation
- Kitemarked to BS EN14604:2005
- 5 year guarantee

















Description

The Eil46e Optical Smoke Alarm is a mains powered alarm with a 9V Alkaline battery back-up and contains a proven optical smoke chamber. The alarm features a new modern design and improved optical sensor with sealed insect mesh and automatic dust compensation for reduced false alarms. It is supplied with an easi-fit base to make it quick and simple to install. Compatible with the Ei168RC RadioLINK Base for wireless interconnection

General Information

Battery Type	Alkaline PP3	Battery weight (kg)	0.036
Depth (mm)	50	Fixings	Screws included
Humidity Range (%)	15-95	Indicators	Green - Power / Red - Alarm or fault
Kitemark reference	522831	Material	HIP UL94 V0 Flame retardant
Packaged weight (kg)	0.389	Paper/cardboard weight (kg)	0.03
Sensor Type	Optical	Plastic weight (kg)	0.002
Power Consumption (W)	0.75	Supply Voltage (V)	230
Product weight (kg)	0.345	Temperature Range (°C)	-10 to 40
Voltage Type	AC	Warranty	5 year warranty
Width (mm)	148		

Technical

Sensor Type	Optical	Indicators	Green - Power / Red - Alarm or fault
Supply Voltage (V)	230	Voltage Type	AC
Battery Type	Alkaline PP3	Power Consumption (W)	0.75

Dimensions & Weights





5 year warranty

 Depth (mm)
 50
 Height (mm)
 148

 Width (mm)
 148
 Product weight (kg)
 0.345

Packaged weight (kg) 0.389

Approvals & Warranty

Certification/ApprovalsBS EN 14604:2005EAN Number5099383010206

Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

Warranty

01691 664100 E enquiries@aico.co.uk W www.aico.co.uk





