# Ei3014

#### Heat Alarm



- Heat sensor responds to heat build-up from large flaming fires (triggers at 58°C)
- Mains powered with Rechargeable Lithium Back-up
- Built in AudioLINK+ data extraction technology
- Easi-fit base for quick and simple installation
- Kitemarked to BS 5446-2:2003





Kitchen



0.009



# Description

**Battery Type** 

The Ei3014 is a mains powered Heat Alarm with 10 Year Rechargeable Lithium Back-up. It contains built-in AudioLINK+ data extraction technology and is upgradeable to SmartLINK wireless interconnection using a Ei3000MRF module

Battery weight (kg)

## General Information

Lithium rechargeable

• • •	3	<i>y y y y</i>	
Depth (mm)	66	Fixings	Screws included
Humidity Range (%)	15-95	Indicators	Green - Power / Red - Alarm / Yellow - Fault
Kitemark reference	83678	Luckins TSI Code	405601583
Material	HIP UL94 V0 Flame retardant	Outer paper/cardboard weight (kg)	0.038
Packaged weight (kg)	0.383	Paper/cardboard weight (kg)	0.064
Plastic weight (kg)	0.002	Sensor Type	Heat (A1)
Supply Voltage (V)	230	Power Consumption (W)	0.25
Product weight (kg)	0.308	Technologies	AudioLINK+
Temperature Range (°C)	-10 to 40	Voltage Type	AC
Warranty	5 year warranty	Width (mm)	150

### **Technical**

Green - Power / Red - Ala ellow -**Indicators Sensor Type** Heat (A1) Fault AC Supply Voltage (V) 230 **Voltage Type Battery Type** Lithium rechargeable Power Consumption (W)

an **Êi** Company



Technologies AudioLINK+

Dimensions & Weights

 Depth (mm)
 66
 Height (mm)
 150

 Width (mm)
 150
 Product weight (kg)
 0.308

Packaged weight (kg) 0.383

Approvals & Warranty

**Certification/Approvals** BS 5446-2:3003 **Warranty** 5 year warranty

**EAN Number** 5099383006506

Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

01691 664100 E enquiries@aico.co.uk W www.aico.co.uk

