

EVOFIRE FIRE RATED DOWNLIGHT 70-100MM CUTOUT IP65 POLISHED CHROME ROUND +GU10 HOLDER INTEGRAL

ILDLFR70D021



The Evofire Fire Rated Downlight is a safe and attractive fitting for a GU10 or MR16 LED lamp. The fully open design of the Evofire does not conceal your lamp in a large metal canister, which can trap some of the heat it generates, lowering lamp lifetime and performance. Lamps installed in an Evofire run at up to 10 degrees C cooler than a typical can-style fire rated downlight from leading LED brands - this can extend the lifetime of your lamps. As well being very tough thanks to its steel construction, The Evofire is also a highly aesthetic choice for Fire Rated lighting. The 1mm blend-in bezel is up to 10 times thinner than typical IP65 rated downlights and fits almost flush with your ceiling, so the downlight looks discreet and pleasing in any setting. This model features an extra wide bezel to cover cut-outs ranging from 70mm-100mm. This downlight is fire rated to 30, 60 and 90 minutes in compliance with BS476 Part 21:1987, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. See installation guide for full details.



Details

Quick Order Code: 991065

Barcode: 5055788238447
Category: Downlights
Range Name: Evofire
Product Type: Fire Rated

Product Body Finish: Polished Chrome

Market Segment: Commercial indoor, Residential indoor

Finish: Polished Chrome

Fixed/Tiltable: Fixed Warranty (Years): 3
CE RoHS: Yes

Physical Data

38

Product Depth (mm): 166

Product Weight (g): Steel, Glass

Material: 110

Overall diameter (mm): Pressed Steel, Glass

Construction: 70-100
Cut Out Diameter (mm): Round

Bulb or Luminaire Shape: Recess mounted

Luminaire Fixing: Indoor, General Lighting

Placement / Application:

Electrical Data

Insulation Guard: No

Light Data

Fire Rating (mins): 30, 60, 90

Environment

CE RoHS: Yes
IP Rating (Back/Recessed side): IP20
IP Rating (Ingress Protection): IP65

Packaging

Package Weight (g): 181
Package Length (mm): 115
Package Width (mm): 115
Package Depth (mm): 70