# EVO LED PANEL LIGHT 1200X300 3600LM 36W 4000K BACKLIT NON-DIMM 100LM/W INTEGRAL

ILP1230B005



This is a 36W, 3600lm 1200x300 Integral LED Evo panel. It delivers a uniform white light across the whole of its surface. The high level of efficacy (100lm/W) offers savings in running cost against traditional 72W fluorescent fittings as well as many other LED panels.

### **Details**

Quick Order Code:	636064
Barcode:	5055788256731
Category:	Panels
Range Name:	Evo
Product Type:	1200 x 300
Product Body Finish:	White
Market Segment:	Commercial indoor
Warranty (Years):	5
CE RoHS:	Yes
Physical Data	
Product Length (mm):	1196
Product Depth (mm):	30
Product Width (mm):	296
Product Weight (g):	1800
Optic:	Opal diffuser
Material:	Aluminium, Steel, PS Diffuser
Construction:	Aluminimum backplate and frame
Luminaire Fixing:	Recessed in ceiling grid, surface mounted or
	suspended (additional surface mounted or suspension
	kit required)
Placement / Application:	Indoor, General Lighting

#### **Electrical Data**

Power Consumption (W) :	30
Power Factor:	0.
Wattage equivalent (W):	80
Dimming:	N

36 0.9 86.4 Non-Dimmable


Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

## **Light Data**


Lumineus Elux in Lumens (Im).	3600
Luminous Flux in Lumens (Im):	3600
Luminous efficacy (Im/W):	100
Peak Intensity (Cd):	1239
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	110
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	50000
Lighting Method:	Back-lit
Switching Cycles:	25000

## **Environment**

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	E
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	20
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging



### Portal.integral-led.com

	2450
Package Weight (g):	1270
Package Length (mm):	375
Package Width (mm):	50
Package Depth (mm):	

## Portal.integral-led.com