


**EVO LED PANEL LIGHT 600X600 3650LM 33W 6500K BACKLIT NON-DIMM  
111LM/W INTEGRAL**

ILP6060B034



This is a 33W, 3663lm 600x600 Integral LED Evo panel. It delivers a uniform white light across the whole of its surface. The high level of efficacy (111lm/W) offers savings in running cost against traditional 72W fluorescent fittings as well as many other LED panels.

**Details**

<b>Quick Order Code:</b>	372655
<b>Barcode:</b>	5055788252108
<b>Category:</b>	Panels
<b>Range Name:</b>	Evo
<b>Product Type:</b>	600 x 600
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	595
<b>Product Depth (mm):</b>	35
<b>Product Width (mm):</b>	595
<b>Product Weight (g):</b>	1600
<b>Optic:</b>	Opal diffuser
<b>Material:</b>	Aluminium, Steel, PS Diffuser
<b>Construction:</b>	Aluminium backplate and frame
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	33
<b>Power Consumption (W) :</b>	33
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	86.4
<b>Amperage (mA):</b>	850
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes



Electric Current: AC  
EN: EN-60598  
LVD Certified: Yes

## Light Data

Luminous Flux in Lumens (lm): 3663  
Luminous efficacy (lm/W): 111  
Peak Intensity (Cd): 1197  
Correlated Colour Temperature (CCT) (K): 6500  
Colour Temperature: 6500K - Cool Daylight  
Colour Temperature Name: Daylight  
Beam Angle: 110  
Colour Rendering Index (CRI): 80  
Frequency Range (Hz): 50/60  
Instant on (Less than 1 second): Yes  
LED Type: Surface mounted device (SMD)  
Lifetime (hours): 35000  
Lighting Method: Back-lit  
Switching Cycles: 17500

## Environment

EN: EN-60598  
LVD Certified: Yes  
CE RoHS: Yes  
New Energy Rating: E  
Hg 0% (Mercury Free): Yes  
IP Rating (Back/Recessed side): IP20  
IP Rating (Ingress Protection): IP20  
Lowest Operating Temperature (°C): -20  
Maximum Operating Temperature (°C): 40  
TP rating: None



## Packaging

Package Weight (g):

2090

[Portal.integral-led.com](http://Portal.integral-led.com)

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

<b>Package Length (mm):</b>	625
<b>Package Width (mm):</b>	600
<b>Package Depth (mm):</b>	42