

# JC050006

# **Toughflood Commercial**

Toughflood Commercial 100W 10800lm 108lpcW 4000K IP65 Black

### **Features & Benefits**

- Up to 108 LpcW
- Driver less technology, instant start up
- Polycarbonate Diffuser: Suitable for food preparation
- 2M pre-wired H05RN-F cable for exterior applications
- ADC12 die-cast aluminium body, corrosion resistant, lightweight for easier installation
- Easy access installation with 55° angled Galvanized steel bracket, 110° beam angle
- This product contains a light source of energy efficiency class E





Depth (mm)











#### **General Information**

Mounting Wall

Trade Name Toughflood

Environment Outdoor
Color Finish Black

Product Shape Rectangular

Product Range Commercial Exterior

IK Rating IK08

Overall Dimensions 322 x 265 x 38mm

Length (mm)265Width (mm)307

Product Weight(kg) 1.8

Light Source LED

Light Source Features Neutral White

Recommended Product Location Exterior, general security lighting

Method Of Fix Mounting Bracket with suitable fixings (not supplied)

38

IP Rating IP65

Origin of manufacturer China

Warranty (See Website for terms and conditions)

Driver Manufacturer No driver, mains LED Chips

LED Manufacturer/Type Optoelectronics 2835

Lighting Product Type 1 Wall Light

Customs Tariff code\*\* 9405421000

## **Electrical**

Voltage Rating 220-240

Primary Running Current(Amp) 0.51

Inrush current(Amps) 30A max peak

Operating Frequency Hz 50/60Hz

Luminaire Circuit Wattage 100

Class

EMC Compliant (EN55015)

Yes

Power Factor Correction

0.9

Input Electrical Connections

Live, Earth and Neutral

Dimmable No

Supplied cable rating 2M pre-wired H05RN-F

### **Thermals**

Operating Temperature Range °C -20 to +40

#### **Performance Data**

LED Life (Hours)\* 54000

This product contains a light source of energy efficiency

Energy Rating

class E

Actual Lumen Output 10800

Lumens Per Circuit Watt 108

Standard Deviation Colour Matching - SDCM <6

Color Rendering Index 50-79

CRI: Ra 70

Correlated Color Temperature 4000K

Beam Angle ° 110

LOR (Light Output Ratio) % 100

Photometry Available Yes

#### Construction

Primary Material ADC12 die-cast alumnium

Outer Diffuser Opaque Polycarbonate

# **Packaging**

Product carton overall dimensions(cm) 33 x 27 x 4.5 cm

Product Packaged Weight(kg) 2

Quantity Per Outer Carton 5

Outer carton(L)- cm 34.2

Outer carton(W)- cm Outer carton(H)- cm

Outer carton Net weight- kg

Outer carton Gross weight- kg

Product Bar Code EAN-13 Number

Outer carton Bar Code ITF-14 Number

## **Standards & Approvals**

Manufactured In Accordance To

CE Marked

**UKCA Marked** 

Date code/Purchase order No.

WEEE Symbol

Certificate Of Conformity

**Accredited Members** 

BS EN 60598-2015,2-1,2-5

Yes

28.2

24.5

10.00kg

10.50kg

5052544105982

15052544105989


Yes

Yes

Yes

Available on request

LIA, ISO9001-2015, ISO14001-2015









\*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

\*\*JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 201 [05/01/2024]