Product Data Sheet



SHARK 6801 BW

SHARK SIXEIGHT



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| Material | Polyamide |
|---------------------|--------------------|
| Filling | Silicone |
| Temp. range min | -20 °C |
| Temp. range max | 90 °C |
| Glow wire test | self-extinguishing |
| Protection class | IP68 |
| Voltage | 0,6 kV - 1 kV |
| Order no. UK | SH6801BW |
| Туре | SHARK 6801 BW |
| Packing unit | 1 |
| ETIM-Classification | EC001169 |

Remarks:

Ampere: 32

Cable Size: (3 core) 2.5 - 6 mm

LxBxH: 190x60x48 mm

Describtion:

SHARK SIXEIGHT IP 68 rated pre-filled gel insulated joint, including modular bolts and gaskets, constant force role springs and earthing braid.

Additional Info:

Ready to use, re-enterable, 100% watertight, 100% dust-tight, suitable for SWA cables, no mixing or pouring, immediate operation, excellent electrical insulation, good mechanical strenght, no expiry date.

13.10.2020

Your Contact:

WISKA UK Ltd.

 $\textbf{Unit 7, Hurling Way} \cdot \textbf{St. Columb Major Business Park} \cdot \textbf{TR9 6SX, St. Columb Major, Cornwall} \cdot \textbf{Great Britain}$

☎ +44-12-08816062 · **■** +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk