

- Complies with BS EN 7895.
- T2 = heat resistance rating (210°C).
- Automatically disconnect power at the contacts when the lamp is removed.
- 50.8mm fixing centres for non-access versions. Use with mounting blocks MB326E/MT.
- Solid brass plungers and copper plated steel springs maintain plunger pressure throughout their long life.
- Body angle of angled battens set at 30°.
- Access lampholders have integral RL624 ceiling rose base and heat resisting PVC tails.
- All pendants incorporate automatic cord grips and sleeve caps for ease of flexible cord stripping.



SEL212

Bayonet Cap Cord Grip Lampholders

Description	Pack qty.	Cat ref.
Safety Cord Grip Lampholders - Short Skirt	20	SEL212
Safety Cord Grip Lampholders - Home Office Shield	20	SEL214



SEL354

Safety Straight Batten Lampholder

Description	Pack qty.	Cat ref.
Three Terminal - Home Office Shield	20	SEL354



SEL96T

Safety Access Batten Lampholder

Description	Pack qty.	Cat ref.
Straight 2 Terminal Body, 3 Terminal and Earth Base - Home Office Shield	10	SEL96T
Angled 2 Terminal Body, 3 Terminal and Earth Base - Home Office Shield	10	SEL106T